

Solid Rubber Wheels and Castors





















Solid Rubber Wheels LINE „VBR“

Wheel:

Wheel body made of sheet steel, zincated, with roller bearing. Equipped with standard solid rubber tyres.

Article no. Wheels	 mm	 mm	 mm	 mm	 kg	
VBR080	80	30	12	40	50	
VBR100	100	30	12	40	70	
VBR125	125	37	15	48	100	
VBR140	140	37	15	48	120	
VBR160	160	40	20	58	135	
VBR180	180	45	20	58	170	
VBR200	200	50	20	58	205	
VBR250	250	60	25	75	300	
VBR280	280	70	25	75	385	
VBR400	400	75	25	75	400	

Available variants (not for all sizes):

All **BOLD** typed articles are usually available from our stock.
All other articles might also be available on short-term, please just ask.



with threadguards
Example.: VBR100FA



with threadguards
Example: VBR100EL



with blue grey tyre
Example: VBR100BG






















Solid Rubber Castors LINE „L/VBR“ „B/VBR“

Housing:

Sheet steel housing shiny zincd, pivot bearing with double ball ring, screwed axle.

Wheel:

Wheel body made of sheet steel, zincd, with roller bearing. Equipped with standard solid rubber tyres.

Article no. Swivel castors	Article no. with lock	Article no. Fixed castors	 mm	 mm	 mm	 mm	 mm	 mm	 mm	 kg	
L/VBR080	L/VBR080/F	B/VBR080	80	30	105	32	105x 85	80x 60	8,2	50	
L/VBR100	L/VBR100/F	B/VBR100	100	30	128	35	105x 85	80x 60	8,2	70	
L/VBR125	L/VBR125/F	B/VBR125	125	37	155	31	105x 85	80x 60	8,2	100	
L/VBR140	L/VBR140/F	B/VBR140	140	37	163	31	105x 85	80x 60	8,2	120	
L/VBR160	L/VBR160/F	B/VBR160	160	40	195	49/56	135x110	105x 80	10,2	135	
L/VBR180	L/VBR180/F	B/VBR180	180	45	225	50/54	135x110	105x 80	10,2	170	
L/VBR200	L/VBR200/F	B/VBR200	200	50	235	50/54	135x110	105x 80	10,2	205	
L3/VBR250	L3/VBR250/F	B3/VBR250	250	60	290	66	135x110	105x 80	10,2	300	
L/VBR250	L/VBR250/F	B/VBR250	250	60	290	70	175x175	140x140	14,2	300	
		B/VBR250	250	60	290	---	232x125	190x 75	14,2	300	

All **BOLD** typed articles are usually available from our stock.
All other articles might also be available on short-term, please just ask.

Please note that the load capacity is reduced with all passing-by hole and stem castors as opposed to castors with a plate.

Available variants (not for all sizes):






















Solid Rubber Wheels LINE „VKR“ „VKG“

Wheel:

Wheel body made of plastic with plain bearing or roller bearing. Equipped with standard set of solid rubber wheels.
(VKG080S = with threadguards)



Article no. Wheels	 mm	 mm	 mm	 mm	 kg	
VKR080	80	30	12	38	50	
VKG080	80	30	12	38	50	
VKG080S	80	35	12	40	100	
VKR100	100	30	12	38	70	
VKG100	100	30	12	38	70	
VKR125	125	37	15	48	100	
VKG125	125	37	15	48	100	
VKR160	160	40	20	58	135	
VKG160	160	40	20	58	135	
VKR200	200	50	20	58	205	
VKG200	200	50	20	58	205	
VKR250	250	60	20	65	275	
VKG250	250	60	20	65	275	

All **BOLD** typed articles are usually available from our stock.
All other articles might also be available on short-term, please just ask.

Available variants (not for all sizes):



with threadguards
Example: VKR100FA



with blue grey tyre
Example: VKG100BGFA
























Example: VKG080S
standard with
threadguards



Solid Rubber Castors
LINE „L/VKR“ „B/VKR“
LINE „L/VKG“ „B/VKG“

Housing:
Sheet steel housing shiny
 zined,
 pivot bearing with double ball ring,
 screwed axle.

Wheel:
 Wheel body made of plastic with
 plain bearing or roller bearing.
 Equipped with standard set of solid
 rubber wheels.

Article no. Swivel castors	Article no. with lock	Article no. Fixed castors	 mm	 mm	 mm	 mm	 mm	 mm	 mm	 kg	
L/VKR080	L/VKR080/F	B/VKR080	80	30	105	32	105x 85	80x 60	8,2	50	
L/VKG080	L/VKG080/F	B/VKG080	80	30	105	32	105x 85	80x 60	8,2	50	
L/VKR100	L/VKR100/F	B/VKR100	100	30	128	35	105x 85	80x 60	8,2	70	
L/VKG100	L/VKG100/F	B/VKG100	100	30	128	35	105x 85	80x 60	8,2	70	
L/VKR125	L/VKR125/F	B/VKR125	125	37	155	31	105x 85	80x 60	8,2	100	
L/VKG125	L/VKG125/F	B/VKG125	125	37	155	31	105x 85	80x 60	8,2	100	
L/VKR160	L/VKR160/F	B/VKR160	160	40	195	49/56	135x110	105x 80	10,2	135	
L/VKG160	L/VKG160/F	B/VKG160	160	40	195	49/56	135x110	105x 80	10,2	135	
L/VKR200	L/VKR200/F	B/VKR200	200	50	235	50/54	135x110	105x 80	10,2	205	
L/VKG200	L/VKG200/F	B/VKG200	200	50	235	50/54	135x110	105x 80	10,2	205	
L3/VKR250	L3/VKR250/F	B3/VKR250	250	60	290	66	135x110	105x 80	10,2	275	
L3/VKG250	L3/VKG250/F	B3/VKG250	250	60	290	66	135x110	105x 80	10,2	275	

All **BOLD** typed articles are usually available from our stock.
 All other articles might also be available on short-term, please just ask.

Please note that the load capacity is reduced with all passing-by hole and stem castors as opposed to castors with a plate.

Available variants (not for all sizes):
















Solid Rubber Wheels LINE „VBR...RD“

Wheel:

Wheel body made of sheet steel, zincd, with roller bearing.
Equipped with half-elastik solid rubber tyres.

Article no. Wheels	 mm	 mm	 mm	 mm	 kg	
VBR100RD	100	30	12	38	100	
VBR125RD	125	37	15	48	120	
VBR160RD	160	40	20	58	225	
VBR200RD	200	50	20	58	350	
VBR250RD	250	60	20	65	450	

Available variants (not for all sizes):



with threadguards
Example: VBR100RDFA


















Solid Rubber Castors LINE „L/VBR...RD“ LINE „B/VBR...RD“

Housing:

Sheet steel housing shiny zined, pivot bearing with double ball ring, screwed axle.

Wheel:

Wheel body made of sheet steel, zined, with roller bearing. Equipped with half-elastik solid rubber tyres.

Article no. Swivel castors	Article no. with lock	Article no. Fixed castors	 mm	 mm	 mm	 mm	 mm	 mm	 mm	 kg	
L/VBR100RD	L/VBR100RD/F	B/VBR100RD	100	30	128	35	105x 85	80x 60	8,2	100	
L/VBR125RD	L/VBR125RD/F	B/VBR125RD	125	37	155	31	105x 85	80x 60	8,2	120	
L/VBR160RD	L/VBR160RD/F	B/VBR160RD	160	40	195	49/56	135x110	105x 80	10,2	225	
L/VBR200RD	L/VBR200RD/F	B/VBR200RD	200	50	235	50/54	135x110	105x 80	10,2	350	
L/VBR250RD	L/VBR250RD/F	B/VBR250RD	250	60	290	70	175x175	140x140	14,2	450	
		B/VBR250RD	250	60	290	---	232x125	190x 75	14,2	450	

Please note that the load capacity is reduced with all passing-by hole and stem castors as opposed to castors with a plate.

Available variants (not for all sizes):



with threadguards
Example: L/VBR100RDFA



with passing-by hole
10,2 or 12,2 mm
Example: LR/VBR100RD
reduced load capacity!



with different pins
Expl.: LZ/VBR100RD
reduced load cap.!

