

Pallet Rollers





































Polyurethane Pallet Rollers LINE „PSK“

Wheel:

Wheel body made of steel with ball bearing. Polyurethane coating firmly poured on, elastic, quiet, abrasion resistant. Low rolling resistance.



Article no. wheels	 mm	 mm	 mm	 mm	 kg	
PSK50/040/15	50	40	15	40	250	
PSK60/040/15	60	40	15	40	250	
PSK70/055/20	70	55	20	55	400	
PSK70/060/20	70	60	20	60	425	
PSK70/070/15	70	70	15	70	500	
PSK75/040/20	75	40	20	40	250	
PSK75/045/20	75	45	20	45	375	
PSK75/070/20	75	70	20	70	550	
PSK75/080/20	75	80	20	80	650	
PSK75/095/20	75	95	20	95	750	
PSK80/030/20	80	30	20	30	250	
PSK80/050/20	80	50	20	50	350	
PSK80/060/20	80	60	20	60	450	
PSK82/050/20	82	50	20	50	400	
PSK82/060/20	82	60	20	60	500	
PSK82/070/20	82	70	20	70	700	
PSK82/080/20	82	80	20	80	800	
PSK82/090/20	82	90	20	90	850	
PSK82/100/20	82	100	20	100	900	
PSK82/110/20	82	110	20	110	1000	
PSK85/050/20	85	50	20	50	450	
PSK85/060/20	85	60	20	60	550	
PSK85/070/20	85	70	20	70	750	
PSK85/080/20	85	80	20	80	850	
PSK85/090/20	85	90	20	90	900	
PSK85/100/20	85	100	20	100	1000	
PSK85/110/20	85	110	20	110	1050	
PSK85/120/20	85	120	20	120	1100	

Different sizes are also available with ball bearing for axle \varnothing 17 and 25 mm. Please change the last two digits in the order no. accordingly.

Example with axle- \varnothing 25 mm : PSK82/100/25

If you need a different installation length, please indicate the desired length before the axle- \varnothing

Example with installation length of 104 mm and axle- \varnothing 25 mm: PSK82/100/104/25

All **BOLD** typed articles are usually available from our stock.

All other articles might also be available on short-term, please just ask.






















Vulkollan® Pallet Rollers LINE „PVSK“



Wheel:

Wheel body made of steel, with ball bearing and plastic seal to protect against spray water and other things.

Vulkollan® coating D15, firmly poured on, elastic, quiet, abrasion resistant, low rolling resistance, high load capacity. Very suitable for electrically powered forklift trucks.

Article no. wheels	 mm	 mm	 mm	 mm	 kg	
PVSK82/070/75/20	82	70	20	75	500	
PVSK85/060/65/20	85	60	20	65	450	
PVSK85/060/65/25	85	60	25	65	450	
PVSK85/070/75/20	85	70	20	75	500	
PVSK85/075/80/20	85	75	20	80	550	
PVSK85/075/80/25	85	75	25	80	550	
PVSK85/080/85/20	85	80	20	85	600	
PVSK85/080/85/25	85	80	25	85	600	
PVSK85/090/95/20	85	90	20	95	700	
PVSK85/090/95/25	85	90	25	95	700	
PVSK85/095/100/20	85	95	20	100	750	
PVSK85/095/100/25	85	95	25	100	750	
PVSK85/100/105/20	85	100	20	105	800	
PVSK85/100/105/25	85	100	25	105	800	
PVSK85/110/115/25	85	110	25	115	850	























Polyamide Pallet Rollers

LINE „KHK“

Wheel:

Made of high quality polyamide with deep groove ball bearing, natural colour.



Article no. wheels	 mm	 mm	 mm	 mm	 kg	
KHK80/070/20	80	70	20	70	700	
KHK80/100/20	80	100	20	100	1000	
KHK82/060/20	82	60	20	60	650	
KHK82/070/20	82	70	20	70	700	
KHK82/080/20	82	80	20	80	800	
KHK82/090/20	82	90	20	90	900	
KHK82/100/20	82	100	20	100	1000	
KHK82/118/20	82	118	20	118	1200	
KHK85/046/20	85	46	20	46	500	
KHK85/061/20	85	61	20	61	650	
KHK85/075/20	85	75	20	75	800	
KHK85/080/20	85	80	20	80	850	
KHK85/090/20	85	90	20	90	950	
KHK85/100/20	85	100	20	100	1100	
KHK85/110/20	85	110	20	110	1200	
KHK85/120/20	85	120	20	120	1300	

Different sizes are also available with ball bearings for axle \varnothing 17 and 25 mm.
Please change the last two digits of the order no. accordingly.

Example with axle- \varnothing 25 mm: KHK82/100/25

If you need a different installation length, please indicate the desired length before the axle- \varnothing

Example with installation length of 104 mm and axle- \varnothing 25 mm: KHK82/100/104/25

All **BOLD** typed articles are usually available from our stock.
All other articles might also be available on short-term, please just ask.



Polyurethane Rollers















LINE „LS/PSK“ „BS/PSK“

Housing:

Solid welded steel construction, zinc chromed, painted black, with groove ball thrust bearing and a tapered ball bearing in the swivel.

Wheel:

Wheel body made of steel with ball bearing. Polyurethane coating firmly poured on, elastic, quiet, abrasion resistant. Low rolling resistance.

Article no. Swivel castors	Article no. Fixed castors	 mm	 mm	 mm	 mm	 mm	 mm	 mm	 kg	
LS/PSK070	BS/PSK070	70	70	127	60	135x110	105x 80	13	500	
LS/PSK075	BS/PSK075	75	70	130	60	135x110	105x 80	13	550	
LS/PSK080	BS/PSK080	80	70	132	60	135x110	105x 80	13	650	
LS/PSK082	BS/PSK082	82	70	133	60	135x110	105x 80	13	700	
LS/PSK085	BS/PSK085	85	70	135	60	135x110	105x 80	13	750	

Low overall height with a high load capacity!



Polyamide Rollers

LINE „LS/KHK“ „BS/KHK“














Housing:

Solid welded steel construction, zinc plated, painted black, with groove ball thrust bearing and a tapered ball bearing in the swivel.

Wheel:

Made of high quality polyamide in solid construction, with ball bearing.

The wheels are temperature resistant -40°C up to 80°C.

Article no. Swivel castors	Article no. Fixed castors									
		mm	mm	mm	mm	mm	mm	mm	kg	
LS/KHK082	BS/KHK082	82	70	133	60	135x110	105x 80	13	700	
LS/KHK082/80	BS/KHK082/80	82	80	133	60	135x110	105x 80	13	800	
LS/KHK085	BS/KHK085	85	70	135	60	135x110	105x 80	13	800	
LS/KHK085/80	BS/KHK085/80	85	80	135	60	135x110	105x 80	13	850	

Low overall height with a high load capacity!